

Product comparison Westone Elite Series

	ES10	ES20	ES30	ES50	ES60	ES80
Sensitivity	114 dB/mW	119 dB/mW	124 dB/mW	120 dB/mW	118 dB/mW	111 dB/mW
Frequency response	20 Hz - 18 kHz	20 Hz - 18 kHz	20 Hz - 18 kHz	8 Hz - 20 kHz	8 Hz - 20 kHz	5 Hz - 22 kHz
Impedance	19 Ohm	27 Ohm	56 Ohm	45 Ohm	45 Ohm	80 Ohm
Driver setup	1 x BA driver	1 x low BA driver 1 x high BA driver	1 x low BA driver 1 x mid BA driver 1 x high BA driver	1 x low BA driver 2 x mid BA driver 2 x high BA driver	2 x low BA driver 2 x mid BA driver 2 x high BA driver	2 x low BA driver 2 x mid BA driver 4 x high BA driver
Cross-over	None	2-way	3-way	3-way	3-way	3-way
Features	Replaceable cable	Replaceable cable	Replaceable cable	Replaceable cable	Replaceable cable	Replaceable cable
Average attenuation	25-28 dB	25-28 dB	25-28 dB	25-28 dB	25-28 dB	25-28 dB
High Resolution Audio			•	•	•	•

BA: Balanced Armature Driver

Vocals	•	•	•		•	•
Guitar player		•	•		•	•
Bass player				•	•	•
Keyboard player			•	•	•	•
Drummer		•	•	•	•	•
Backing vocals	•	•			•	•
Brass player			•		•	•
Sound engineer			•		•	•