



In-Ears

'Go to the max' met Variphone In-Ear monitors

Specificaties

	1 Symphony	Go 2 Rock	3 For Live	Quad	6 Without Limits
Gevoeligheid	109 dB/mW	109 dB/mW	115,5 dB/mW	116 dB/mW	119 dB/mW
Frequentierespons	25 Hz - 20 kHz	18 Hz - 20 kHz	18 Hz - 20 kHz	16 Hz - 20 kHz	10 Hz - 20 kHz
Impedantie	50 Ohm	75 Ohm	28 Ohm	19 Ohm	18 Ohm
Driver setup	1 x BA Driver	1 x laag BA driver 1 x hoog BA driver	2 x laag BA driver 1 x hoog BA driver	2 x laag BA driver 1 x mid BA driver 1 x hoog BA driver	2 x laag BA driver 2 x mid BA driver 2 x hoog BA driver
Cross-over	Geen	2-weg	2-weg	3-weg	3-weg
Kenmerken	Vervangbare kabel	Vervangbare kabel	Vervangbare kabel	Vervangbare kabel	Vervangbare kabel
Gemiddelde demping	28 dB	28 dB	28 dB	28 dB	28 dB
High Resolution Audio				•	•

BA: Balanced Armature Driver

Vocals	•	•	•		•
Gitarist		•	•		•
Bassist				•	•
Toetsenist			•	•	•
Drummer		•	•	•	•
Backing vocals	•	•	•		•
Blazers			•		•
Sound engineer			•		•

VARIPHONE

Safe and sound hearing

Variphone International

Deusterstraat 72 | 3990 Peer (B)
+32 (0)11 – 66 81 20

Variphone Nederland

Netwerk 11 | 1446 XB Purmerend (NL)
+31 (0)299 – 40 44 49

variphone.com
contact@variphone.com
variphone

Accredited
Service Provider
HearingCoach®